



specguard

SPECGUARD SG50 SHINGLE SAVER ROOF EXTENDER

PRODUCT DISCRIPTION

SG50 Shingle Saver roof extender is formulated with premium modified acrylic resins, designed to rejuvenate aged and worn shingles roofs. When applied it will give worn dried out, brittle roof shingles additional years of useful life.

SG50 Shingle Saver is milky white when applied and dries to an amber clear that will enhance the appearance of the existing roof.

SHINGLE SAVER APPLICATION PROCESS:

- Clean and power wash the entire roof surface
- Make any necessary repairs eliminating all leaks
- Protect all surrounding areas for potential over spray
- Apply the **SG50 Shingle Saver** by spraying or roller application. The product can be applied thru an airless sprayer, pump Hudson sprayer, and roll applied.
- Repeat the process applying 2-3 coats depending on the roof conditions.

PRODUCT BENEFITS AND FEATURES:

- **SG50 Shingle saver** is easy to apply is a UV stable product that will add additional life to your existing roof
- Restores resilience and flexibility to worn shingles
- Reduces roof granule loss
- **SG50 shingles saver** contains antifungal agents and biocides to help prevent mold and mildew growth
- Eco –Friendly contains no solvents or VOC's
- Protects against damaging UV rays
- Restores the aesthetic look of the shingles

SG50 SHINGLE SAVER PRODUCT DATA

- Color: Clear (dry), When applied: Milky White
- Vehicle Base: 100% Modified Acrylic Resin
- Weight per Gallon: 8.5 lbs.
- Solid by Weight: 44 + 2%
- Viscosity: @ 77°F 400 cps
- Dry Film Thickness: @ 1 gal/100 sq. ft 3.5 mils
- Dry Time: 1 hour @ 72F
- Coverage: 100-125 Square Feet Per Gallon Depending on Surface Porosity
- Application temperature 50° F or above
- Weather conditions require a 24 hour none rain window for proper product application dry time

SG50 SHINGLE SAVER PRODUCT is designed with a unique combination of key components, along with innovative modified, self-crosslinking acrylic resins providing long term durability even in harsh weather conditions.

- Strong mechanical properties with high tensile and high elongation properties.
- Maintains strong mechanical properties even in extended weathering cycles
- Excellent adhesion to Asphalt shingle surfaces



Power wash the roof and repiar all leak areas



SG50 Shingle Saver Spray Applied



SG50 Shingle Saver Roller Applied



SPECGUARD COATING SYSTEMS

Rialto CA 92376

E-mail: sales@specguard.us / Phone direct: 310-722-7516

ISO 9001:2015 Certified QMS Manufacturer